

Discfuser® Diffuser

Discfuser® diffusers are recommended for applications where coarse bubble diffusion is satisfactory, or dictated by the presence or expectation of high solids concentration in the aerated liquor.

The Siemens Discfuser® consists of three elements: An ABS housing; a stainless steel retaining ring; and a PVC movable disc. The movable disc is inserted between the diffuser housing and the stainless steel retaining ring, and is free to rise and fall within the space provided between the housing and the retaining ring.

As air is discharged through the diffuser, the disc rises and air is permitted to pass around the entire periphery of the diffuser into the liquid.

In the event of a power failure, or if the air supply is interrupted for any reason, the hydrostatic pressure of the liquid above the diffuser will force the disc against the diffuser housing.

This prevents the passage of mixed liquor into the air supply piping which could result in excess solids accumulating within the air piping system.

Discfuser® diffusers are available with control orifices in five diameters. Proper orifice selection at the time of application and installation ensures uniform air distribution throughout the tank contents, while optimizing the headloss through the system.

In addition to being used in aeration tanks, Discfuser® diffusers are successfully used in aerated grit removal systems, aerobic digester and channel mixing applications.

SIEMENS

Benefits

- Prevents backflow of solids
- Minimum controlled headloss
- Corrosion resistant construction



The information provided in this brochure contains merely general descriptions or characteristics of performance which in actual case of use do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of the contract.

Discfuser is a trademark of Siemens, its subsidiaries or affiliates.

